



RTRT.E14847 Receptacles for Plugs and Attachment Plugs

Page Bottom

Receptacles for Plugs and Attachment Plugs

See General Information for Receptacles for Plugs and Attachment Plugs

AMPHENOL INDUSTRIAL OPERATIONS

E14847

40-60 DELAWARE AVE
SIDNEY, NY 13838-1304 USA

Midget NEP-LOC Line: Receptacles, 20 amp, 125 v, ac, 15 amp, 125 v, dc, 10 amp, 277 v, ac or 250 v, dc, Cat. No. RMCA, RMCBB, RMCBR, RMCP, RMCR, RMEA, RMEBB, RMEBR, RMEP, RMER, RMLA, RMLBB, RMLBR, RMLP or RMLR followed by numerical suffix 1, 2 or 3, followed by 15, followed by 2, 3 or 4 followed by 21 and may be provided with additional suffix G on 4-pole device only with or without additional suffix B, C, H, I, L, R or Y.

Motor attachment caps, 20 amp, 125 v, ac, 15 amp, 125 v, dc, 10 amp, 277 v, ac or 250 v, dc, Cat. No. RMCA, RMCBB, RMCBR, RMCP, RMCR, RMEA, RMEBB, RMEBR, RMEP, RMER, RMLA, RMLBB, RMLBR, RMLP or RMLR, followed by numerical suffix 1, 2 or 3, followed by 15, followed by 2, 3 or 4, followed by 22, with or without the additional suffix G on 4-pole device only with or without additional suffix B, C, H, I, L, R or Y.

Cord connector bodies, rated 20 amp, 125 v, ac, 15 amp, 125 v, dc, 10 amp, 277 v, ac or 250 v, dc, Cat. Nos. RMCD, RMED, RMLD followed by a numerical suffix 3, 4, 5 or 31, followed by 15, followed by 2, 3 or 4, followed by 22, with or without the additional suffix G on 4-pole device only, with or without additional suffix M or K, with or without additional suffix B, C, H, I, L, R or Y.

Plugs, rated 20 amp, 125 v, ac, 15 amp, 125 v, dc, 10 amp, 277 v, ac or 250 v, dc, Cat. No. PM followed by suffix C, E or L, followed by suffix D, followed by a numerical suffix 3, 4, 5 or 31, followed by 15, followed by number 21, with or without additional suffix G on 4-pole device only with or without suffix K or M, with or without additional suffix B, C, H, I, L, R or Y.

"Quelarc" Receptacles, 20, 30, 60 or 100 amp, 250 v, dc, 600 v, ac, Cat. Nos. JRC, JRCA, JRCA, JRCCB, JRCCBE, JRCC, JRCCCE, JRCD, JRDA, JRDB, JRDBB, JRDBE, JRDC, JRDCCE, JRE, JREA, JREA, JREB, JREBB, JREBE, JREC, JRECE, JRKD, JRL, JRLA, JRLB, JRLBB, JRLBE, JRLC, JRLCE, JRPC, JRPP, JZCA, JZCB, JZCBB, JZCBE, JZCC, JZCCE, JZDA, JZDB, JZDBB, JZDBE, JZDC, JZDCE, JZEA, JZEB, JZEBB, JZEBE, JZEC, JZECE, JZKD, JZLA, JZLB, JZLBB, JZLBE, JZLC, JZLCE, JZPC, JZPP, KRC, KRCA, KRCB, KRCCB, KRCCBE, KRCC, KRCCCE, KRCD, KRDA, KRDB, KRDBB, KRDBE, KRDC, KRDCCE, KRE, KREA, KREB, KREBB, KREBE, KREC, KRECE, KRKD, KRL, KRLA, KRLB, KRLBB, KRLBE, KRLC, KRLCE, KRPC, KRPP, KZCA, KZCB, KZCBB, KZCBE, KZCC, KZCCE, KZDA, KZDB, KZDBB, KZDBE, KZDC, KZDCE, KZEA, KZEB, KZEBB, KZEBE, KZEC, KZECE, KZKD, KZLA, KZLB, KZLBB, KZLBE, KZLC, KZLCE, KZPC, KZPP with four-, five-, six- or seven-digit suffix numeral;

200 amp, 250 v, dc, 230 v, ac, for current interruption; 600 v, for disconnect only, Cat. Nos. JRC-3200, JRCCB-720036, KRC-3200, KRCCB-720036.

"Quelarc" Plugs, 20, 30, 60 or 100 amp, 250 v, dc, 600 v, ac, Cat. Nos. JPC, JPD, JPF, JPLD, JWPC, JWPD, JWPF, JWPLD, KPC, KPD, KPF, KPLD, KWPC, KWPD, KWPF, KWPLD with five-, six-, or seven-digit suffix numeral;

200 amp, 250 v, dc, 230 v, ac, for current interruption; 600 v, for disconnect use only, Cat. Nos. JPM-2120036, KPM-2120036.

Receptacles, 30 amp, 250 v, dc, 600 v, ac, Cat. Nos. 221, 321, 421 with suffix letters R, N, O, Q, with additional suffix letters A, B, C, D, E, F, G, H, M, U, V, with or without additional suffix numbers -1, -2, -3, -4, may be followed by other suffixes;

60 amp, 250 v, dc, 600 v, ac, Cat. Nos. 222, 322, 422 with suffix letters R, N, O, Q, with additional suffix letters A, B, C, D, E, G, H, V, with or without additional suffix numbers -3, -4, -5.

Cord connectors, 30 amp, 480 v, ac, Cat. No. P-208295 ;

30 amp, 250 v, dc, 600 v, ac, Cat. Nos. 221, 321, 421 with suffix letter X, with additional suffix letters C, G, H, K, M, N, R, T, with or without suffix numbers -1, -2, -3;

bodies, Cat. Nos. 221, 321, 421 with suffix letter H, with additional suffix letters C, G, H, K, M, N, R, T, with or without suffix numbers -1, -2, -3;

60 amp, 250 v, dc, 600 v, ac, Cat. Nos. 222, 322, 422 with suffix letter X, with additional suffix letters C, G, H, K, M, N, R, T, with or without suffix numbers -3, -4, -5;

bodies, Cat. Nos. 222, 322, 422 with suffix letter H, with additional suffix letters C, G, H, K, M, N, R, T, with or without suffix numbers -3, -4, -5.

Plugs, 45 amp, 600 v, ac, Cat. Nos. B-321-PNO, 20-P-27 ;

60 amp, 250 v, dc, 600 v, ac, Cat. No. 322 with suffix letter P, with additional suffix letters C, G, H, K, M, N, R, T, with or without suffix numbers -3, -4, -5;

100 amp, 250 v, ac, Standby Series 75, Cat. Nos. JBD, JBDE, JDE, JED, JPD, JPFD, JPLD, KAPD, KAPE, KBPD, KDPE, KEPD, KWPD, KWPLD with suffix numerals of 3, 4, 5, or 6 digits followed by suffixes "AG" or "PRAG".